

SWIMMING POOL DEHUMIDIFIERS



TECHNICAL DATA

		Pool surface	Extraction rate 30°C / 60%RH	Extraction rate 30°C / 80%RH	Air flow	Noise level (at 1 m dist.)	Power consumption	Heat output	Refrigerant	Dimensions netto (W x H x D)	Weight netto / brutto
SERIES	Model	m ²	l/24hrs	l/24hrs	m ³ /h / Pa	dB (A)	W	W		mm	kg
DRY 300	PLASTIK	30	36	48	550	42	700	1900	R410A	780 x 660 x 255	40 / 46
	SILVER									780 x 642 x 300	50 / 56
	METAL									780 x 660 x 255	40 / 46
	TTW									780 x 660 x 255	40 / 46
DRY 400	PLASTIK	45	48	58	600	42	700	1900	R410A	780 x 660 x 255	40 / 46
	SILVER									780 x 642 x 300	50 / 56
	METAL									780 x 660 x 255	40 / 46
	TTW									780 x 660 x 255	40 / 46
DRY 500	PLASTIK	60	66	101	800	44	1000	3500	R410A	1245 x 660 x 255	60 / 73
	SILVER									1245 x 660 x 300	77 / 90
	METAL									1245 x 660 x 255	60 / 73
	TTW									1245 x 660 x 255	60 / 73
	DUCT	50	52	68	1000 / 200	56	1150	3500		1245 x 660 x 253	75 / 88
DRY 800	METAL	90	90	136	1100	46	1600	5100	R410A	1250 x 950 x 310	100 / 133
	TTW									1247 x 950 x 300	102 / 135
	DUCT	80	88	135	1100 / 170	58	1700	5100		1250 x 950 x 310	104 / 136
DRY 1200	METAL	120	120	181	1200	46	2150	5250	R410A	1250 x 950 x 310	104 / 136
	TTW									1247 x 950 x 300	103 / 136
	DUCT	110	112	170	1200 / 145	60	2250			1250 x 950 x 310	104 / 136